



Project Overview

110 Miles

Of rockfall-prone highway to evaluate

12 Corridors

Spread around Northwest New Mexico

10 Highways

Mostly rural

Inventory

Inventory rockfall sites

Assess


Categorize rockfall hazard

Prioritize

Conceptual mitigation design and costing



Project Overview





Methodology

- 1 Desktop Inventory
- 2 Develop Rockfall Ranking Rating System (Class 1 to 3)
- Field Investigation and Verification
- 4 Develop Online ArcGIS System
- 5 Meeting with Maintenance Patrols
- Develop Conceptual Mitigation Design and Cost Estimates
- 7 Summarize Results and Develop Power BI Dashboard





Desktop Inventory

- 1 Google Earth / Streetview
- 4 Environmental

2 240 RHRS records

5 Land Ownership / ROW

3 Crash Data

6 Populate ArcGIS Online





Project Rockfall Ranking System



Class 1

The most significant impact to safety and in some cases, maintenance and mobility. To be mitigated first.



Class 2

Intermediate sites, but still relatively high risk. Group with Class 1 sites where it makes sense.



Class 3

Judged to be low hazard and consequence of rockfall, or sites with existing mitigation.



ArcGIS Survey123





Boots on the Ground Visited ~200 sites

Field Investigation

ArcGIS Survey 123 form

Confirm Deskop Data

Revise Site Class on AGOL

Propellers in the Air

Drone data at 10 sites

Used for existing fence inspections - Very useful for very large area

3D Models at more complex sites


Interval Length AGOL (miles)

AGOL MP End 80.92

Last Update By



ArcGIS Online Interface (AGOL)



Front End for Inventory

Length of slope hazard
Approximate slope height
Block sizes
Existing mitigation

Ditch configuration and condition Rockfall hazard class

Visualization of 3d Meshes

Safely view site


Measure for quantities

Review Photos and Mitigation

Useful for Patrol meetings



AGOL For 3D Data





Environmental and Right of Way Screening Criteria

1 Land Ownership

4 NPS / BLM / USGS Sensitive Areas

2 Critical Habitat

- 5 Cultural Resource Boundaries
- 3 National Wetland Inventory
 - ROW Data Availability and Mitigation Impact






Meetings with Maintenance Patrols



Perhaps MOST Important!
Institutional / practical knowledge
9 different orgs/patrols
Help estimate frequency / severity
Preference for mitigation option



Primary Rockfall Site Database



Built from Scratch

Microsoft Access Front End Data stored on SharePoint List Back End Sites

Build Mitigation Estimates Sites

- Mitigation Options (e.g. Mesh Mitigation)
 - + Mitigation Elements (e.g. Scaling by the hour, Mesh by the sq. ft., ditch ex. By the lf, etc)

Cost estimates by site, and aggregated Unit costs common throughout project QC Tools

wsp



Conceptual Mitigation Design

Mitigation Options

Ditch cleanout

Scaling

Temporary concrete barrier

Soil or rock excavation

Draped mesh

Pinned mesh

Rockfall Fence

Soil Nail wall

MSE wall rockfall barrier

Selection Criteria

Technical

Cost (capital and maintenance)

District and maintenance

preference

ROW and adjacent land

ownership

Environmental and cultural



Cost Estimating

System Level Cost Estimating

Previous NMDOT and CDOT costs

Simplifying assumptions

Built using database

Simple measurements for quantities

temType	Item Name	Units	Unit Cost	Description	Cost Notes
System Level	Attenuator Fence	LF	\$2,000.00		Estimate from CO 133, Firehouse cut
System Level	Cable Lashing	LS	\$1.00	Cable lashing with anchors, cables, turnbuckles, and mesh. Need to specify actual cost in quantities.	You need to specify actual \$ in quantities. One recent cable lashing project we worked on for a approx. 11' boulder had estimates ranging fron \$20k to \$40k.
System Level	Concrete Barrier (Temporary)	LF	\$75.00		Per Roger.
System Level	Concrete Barrier (Temporary) - Reset	LF	\$20.00	Moving existing temporary barrier to do something and then moving it back later.	From CDOT Bid-tabs. RMP 1/29/2021
System Level	Excavation - Rock	CY	\$100.00	General rock excavation.	
System Level	Excavation - Rock for Ditch	LF	\$100.00	Rock excavation to clean out ditch, assumed to be about 1CY/LF.	Assumes 1.0 CY per LF at \$100/CY
System Level	Excavation - Soil for Ditch	LF	\$30.00	Excavation to clean out ditch, assumed to be about 1CY/LF.	Assume 1.0 CY per LF at \$30/CY
System Level	Excavation - Soil Slope	CY	\$50.00	General excavation to cut back a soil slope.	
System Level	Excavation - Trim Blasting	CY	\$35.00	Trim blasting for laying back a slope. Includes hauling	Based on Mike's I-40 E of Parks derivation. Applicable for larger, production oriented blasting projets. For smaller volumes, use Excavation-Rock. Includes blasting, loading, at hauling (20 mi, 6 trucks).
System Level	Mesh - Draped, Heavyweight	SF	\$12.00	Heavy duty draped mesh, such as cable net with secondary mesh.	
System Level	Mesh - Draped, Midweight	SF	\$4.00	Typical draped mesh.	
System Level	Mesh - Fix Existing, Lightweight	LF	\$340.00		Assume 10' mesh replacement per linear foot. From US 550 study.
System Level	Mesh - Fix Existing, Midweight	LF	\$330.00		Assume 10' mesh replacement per linear foot. From US 550 study.
System Level	Mesh - Pinned, Heavyweight	SF	\$37.00	Pinned mesh system consisting of a heavy weight mesh (e.g. Cable Net) plus secondary mesh and rock bolts.	Adds draped mesh and pattern bolting.
System Level	Mesh - Pinned, Midweight	SF	\$29.00	Pinned mesh system consisting of a mid- weight mesh (e.g. Tecco), and rock bolts.	Adds draped mesh and pattern bolting.
System Level	Retaining Wall MSE - Two-Sided	LF	\$1,200.00	Assuming about 16' high, 12' wide.	From 133 Penny Hot Springs.




Results of Inventory

Worst Sites Rose to Top

Over \$25M (geohazard costs) to fix everything for Class 1

Translates to roughly \$45M total project costs

Now what?





Next Step: Grouping Sites Into Projects



Possible Groupings

In-house maintenance opportunities
Scaling project or on-call
Worst first
One or two Class 1, Plus nearby Class 2
Similar environmental requirements


Key Learnings

Select more sites than you can realistically afford to construct

Try to group similar construction techniques Keep construction cost to \$4-5M max



Power BI Dashboard Interface





Best Practices and Future Improvement



Database is Key

Connection between GIS and primary database

More robust database back end

Improved usability

Room for expansion

Quick and Accurate Site Assessments

No substitute for experience

High-level cost estimates are key for planning

Talk to maintenance forces!!!


Helping the Client

Help package projects (PowerBI!!)

Expand to or integrate with Geotechnical Asset Management (GAM)



Currently Ongoing D2 Rockfall Study





NMDOT D2 Study - US 82 AGOL Model

US 82 Screencast 1

2024-11-15 16:46 UTC

Recorded by Post, Randy

Organized by Post, Randy



D2 Field Investigation



Thank you



in **y** f ⊙ **□**

wsp.com