



Lessons from Poplar Creek, VA: The Deepest Precast Box Culvert in the U.S.


Dr. Eric Jacques
Associate Professor & Murray Family Fellow
Dept. Civil and Environmental Engineering
ejacques@vt.edu | 540-231-2903



STGEC | September 18, 2025

*The research in this presentation is supported by the Virginia Department of Transportation (Contract 124654).
Any opinions expressed are these of the authors and do not necessarily reflect those of the sponsor.*

Why this matters




Today's Roadmap

- Project in a Nutshell
- Design & Construction Challenges
- Field-Monitoring Data
- Interpreting Field Data through Soil-Structure Interaction Models
- Next Steps & Acknowledgements
- Discussion

01

Project Overview

Poplar Creek Culvert



- Route 121-460, ADHS Corridor Q
- Precast concrete triple box culvert
- 2,250 linear feet long
- Total 1,146 precast box sections (~382 boxes per barrel)

Our scope is to conduct a retrospective review of design practices and field measurements to develop design recommendations.

-



Site and Subsurface Conditions

- Subsurface profile: ± 30 ft of alluvium over McClure Sandstone, with interbedded shale layers and occasional coal seams.
- Fill material: Blasted shot-rock aggregate. Particle sizes up to ≈ 36 in.
- Placement: 48 in lifts; fill spread by dozers and “kneaded” by repeated passes of off-road haul trucks – no vibratory rollers.



Construction




Embankment Today



02

Challenges

Do any DOT's have deep buried culverts?





36 states responded

- 70% have fill heights > 35 ft
- 50% cited insufficient guidance in design codes, leading many to avoid such projects due to uncertainties.
- Many reported maintenance and durability issues
- 45% report considering earth pressure as purely geostatic ($\gamma \times H$)

Soil-Structure Uncertainties

Unknown	Why It Matters
Deep-burial stress distribution	Sets design loads. Get it wrong – cracking, costly over-build, or worse.
Shot-rock properties (36 in “max”)	Controls the analysis; hard to measure uniformly; compaction.
Post-construction settlement	Controls timeline for paving highway; differential settlement of boxes; long-term serviceability.
Internal force paths, detailing, and materials	Dictates rebar layout, wall thickness, corrosion protection and durability.
Limits of current SSI models	Constrains confidence; need for shot-rock constitutive models; uncertainty about 3-D effects; nonlinear FE.
Lack of precedent & code guidance	Few comparable cases; commercial tools unvalidated.

Instrumentation Plan – 240 ft and 310 ft




03

Field Measurements


Pressure Results – 240 and 310 ft Sections

- Pressures continue to rise after 240 ft filling has completed?



240 ft Top Pressures



310 ft Top Pressures



Pressure at 240 ft. and 310 ft. Sections





- Design: FLAC 2D Plane Strain,
 $\gamma = 137.5 \text{ pcf}$
- Prelim Design: BOXCAR,
 $\gamma = 137.5 \text{ pcf}$
- #1 Avg. #2 | Measured

?????

Concrete Strain Highlights – 310 ft section

- Measured strains are reasonable, suggest complex load path
- Provide a valuable basis for FE back-estimation of soil pressures under deep fill

Strain Gauge Locations



04


Modeling

3D Culvert and Embankment Model



Goal: Assess 3D effects on fill-culvert interaction to verify pressure readings

- FE Software PLAXIS 3D
- Base model: Hardening soil model ("equivalent" to design constitutive model and assumed input values), monolithic culvert structure, actual bedrock elevation, no valley, straight alignment
- Baseline model for parametric analyses:
 - Subbase material properties
 - Shot rock strength, stiffness, density
 - Bedrock elevation
 - Valley topography
 - Culvert alignment
 - Soil-culvert interface
 - Secondary consolidation

3D Culvert and Embankment Model



310 ft Parametric Study - All Cases Comparison



3D Parametric Study: Key Findings (310-ft embankment)

- Across all mechanisms tested, crown pressure varies within $\pm 10\%$ of baseline.
- A 2D plane-strain model is sufficient for design; 3D effects are second-order.
- The observed pressure irregularities could not be reproduced numerically \rightarrow most likely installation/measurement artifacts rather than physics.



05


Culvert Performance

Culvert Inspection - Joint Distress

- **Flexural cracking** in top and bottom slab
- **Shear cracks** in vertical sidewalls of select barrels
- **Joint distress at many interfaces**, consistent with shear transfer & differential movement between adjacent boxes




-  Typical extent of spalling
-  Max. extent of spalling




Shear Deformation Mode

Joint Distress Locations


- Joint distress concentrated in the mid-slope zones along the embankment side slopes – not at the crest or toe.
- Nonlinear 3D FEA using the as-built undercut profile predicts peaks in longitudinal shear, $|V(x)|$, at consistently x-stations.






InSAR Embankment Settlement

Settlement (in.)



Surface Settlement (in.)



06

Synthesis

Summary and Next Steps

- **Sensor Readings:** Problems with earth pressure sensor data interpretation related to installation. Higher degree of confidence in strain data.
- **Analysis:** Models cannot reproduce the irregular pressure patterns at 240 ft & 310 ft → readings are likely impacted by instrumentation/installation artifacts.
- **Performance:** Structurally, the culverts are generally behaving well. Embankment settlement continues and is being monitored → long term behavior?
- **Critical issue:** Culvert joint details are the weak link → maintenance issue. Research to develop structural box culvert joints is needed.
 - Ongoing: explicit culvert-to-culvert interface modeling.
 - Pending: results of the post-construction deformation survey.
 - Evaluate redesign alternatives: (1) improved precast joint details, (2) cast-in-place culvert with expansion joints, (3) local soil reinforcement to promote composite action.

Acknowledgements

Virginia Tech

Prof. Alba Yerro Colom

Prof. Ioannis Koutromanos

Dr. George Tharakan

Mr. Sukrityranjan Samanta

VDOT

John Bechtold (Bristol District)

VTRC

Ed Hoppe

William Bassett

Kendall Walus

Emad Iskander

Andy Zickler

Ramesh Neupane

Micah Ceary

Lewis Lloyd

VDOT Contractors

Mark Hill*

Kristy Plummer*

BDI, S&ME, Prof. Micheal Seek

** Special thanks for many of the photos in this presentation*



Thank you!

Feel free to contact us – we welcome your feedback and expertise!



Eric Jacques, Ph.D., P.Eng.


Associate Professor and Thomas M. Murray Family Faculty Fellow
The Charles E. Via, Jr. Department of Civil and Environmental Engineering
Virginia Polytechnic Institute and State University

ejacques@vt.edu

<http://www.ericjacques.com/>

(540) 231-2903 (office)

Linear-Elastic Shot Rock: Upper-Bound



- Modeled shot rock as linear elastic with upper-bound stiffness and an unrealistically high unit weight → **deliberate worst-case**
- **Use case:**
 - Conservative preliminary analysis for member sizing.
 - Final design should use measured/typical unit weight and nonlinear, stress-dependent modulus.